

HyFlex® 11-927

MECHANICAL PROTECTION

 OIL-REPELLENT

 M MEDIUM

REF. #	SAMENSTELLING	GAUGE	VOERING-MATERIAAL	COATING-MATERIAAL	COATINGSTIJL EN - PATROON	MANCHET-STIJL	KLEUR	EN-MAAT	LENGTE MM	VERPAKKING
11-927 	Knitted	13	Nylon HPPE	Nitrile	¾ Dipped	Knitwrist	Light grey, dark grey and black	6, 7, 8, 9, 10, 11	215-242	12 pairs in a bag, 12 bags in a carton



Ultimate performance for oily environments

BELANGRIJKSTE SECTOREN



IDEALE TOEPASSINGEN

- Handling & assembly of sharp components with oil/grease coating
- Handling of machined parts coated with light oil
- Assembly of engine & transmission drive trains
- Light metal presses
- Machining, metalworking
- Maintenance
- Body shops
- Primary assembly

BESCHRIJVING

- The first HyFlex® glove to combine advanced cut resistance, oil repellence and oil grip in a single flexible glove. Ideal for handling sharp metal components coated in oil or lubricant.
- Patented Ansell Grip™ technology uses microscopic channels to wick away oil & moisture from part surfaces and tools, providing industry-leading wet and oil grip for added safety and efficiency.
- The design combines a ¾ nitrile dip with grip. This ensures EN Level 4 abrasion protection and long-lasting EN Level 3 cut resistance.
- The ¾ dip geometry means extra protection against oil exposure and knuckle abrasion.
- A new former shape offers superior fit. Together with a highly flexible polymer and a wide range of sizes, this enables more agility in medium-duty applications.
- Greys and blacks mask dirt in oily, grimy and gritty environments.

OPMERKINGEN

- Fit for special purpose

BAANBREKENDE TECHNOLOGIE



EN 388
4342

CATEGORY II

Gedrukt op: 09-10-2015

Ansell Healthcare Europe N.V. (European Head Office)

Riverside Business Park, Block J

Boulevard International 55, 1070 Brussels, Belgium

Tel. +32 (0) 2 528 74 00 • Fax +32 (0) 2 528 74 01 • Fax Customer Service +32 (0) 2 528 74 03

<http://www.ansell.eu> • E-mail info@ansell.eu