

DIGITAL SOUND LEVEL METER WITH USB INTERFACE

MS6701

MS6701

RANGE

30dB~130dB

FREQUENCY

30Hz~8KHz

dB Hz MEM

AUTO Apo F/S

MAX A/C USB



Features:

- ▶ Sound Level Range: 30dB~130dB
- ▶ Large Digital LCD Display with Bar Graph
- ▶ Fast/Slow Selection
- ▶ Weighting A/C Selection
- ▶ Date and Time Display
- ▶ AC/DC Auxiliary Output
- ▶ Data Logging and USB Interface
- ▶ Back Light and Auto Power Off

Specifications

MS6701

Specifications	Range
Measurement Range	30dB~130dB
Accuracy	±2dB
Resolution	0.1dB
Display	2000 counts
Sample Rate	2 times/s
Frequency Range	30Hz~8KHz
Data logging	16000 records
Over Range Indication	"UNDER" / "OVER"
Auxiliary Output	AC: 0.707 Vrms at Full Range for Each Level, Impedance 600Ω DC: 10mV/dB, Impedance 100Ω
Analog Bar Indication	●
Auto range & Manual range	●
Auto power off	●
Fast/Slow Selection	●
MAX Value Hold Function	●
A/C Weighting Selection	●
Date And Time Display	●
USB Interface	●
Display Backlight	●
Low Battery Display	●
General	
Power Supply	6×1.5V AAA Batteries
Product Size	265mm×80mm×69mm/ 10.4"×3.15"×2.7"
Product Weight	317g/0.7lb

