

Miller Manyard® Shock-Absorbing Lanyard

Description

The Manyard Shock-Absorbing lanyard features a special woven shock-absorbing inner core that reduces fall arrest forces. The heavy-duty tubular outer jacket serves as a back-up web lanyard.

Materials

Webbing:

- Safety Strap/Jacket: tubular polyester
- Shock-absorbing web core: polyester, 1" POY

Label: Valeron

Thread: 6 cord bonded 3 strand polyester

Hardware: Steel

- Locking Snap Hooks: 3/4 in. (19mm) gate opening
- Locking Rebar Hooks: 2 1/2 in. (63mm) gate opening

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

Max. Working Load: 310 lbs (141 kg)

Minimum Tensile

Webbing: 5,000 lbs. (22kN)

Thread: 42 lb. (0.18kN)

Hardware: 5,000 lbs (22kN)

Certification

OSHA 1926.502, 1910.66; ANSI A10.32 and CSA Z259.11



SKU	Material	# Legs	Lanyard Connection	Anchorage Connection	Special	Standard Length
216WLS/6FTYL	Polyester	1	Locking snap hook	Locking snap hook	Warning flag	6-ft. (1.8m)
219WRS/6FTYL	Polyester	1	Locking snap hook	Locking rebar hook	Warning flag	6-ft. (1.8m)
231WRS/6FTYL	Polyester	2	Locking snap hook	Locking rebar hooks	Warning flag	6-ft. (1.8m)
232WLS/6FTYL	Polyester	2	Locking snap hook	Locking snap hooks	Warning flag	6-ft. (1.8m)
233WLS/6FTYL	Polyester	1	Chock-off loop	Locking snap hook	Warning flag	6-ft. (1.8m)



by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.