

ARC PROTECTION BLANKETS AND SWITCHBOARD MATTING



MEETS NEW ASTM F2676 STANDARD



WARNING: Because of the unpredictability of electrical Arcs, the Arc Protective Blanket (APB) may not totally contain the arc and flashes, but only reduce or limit explosive and incendiary effects. Properly installed APB's can reduce the risk of injury from the blast and heat, however they do not provide any personal protection for but not limited to Hearing, Eyes, Smoke/ Hazardous gases inhalation and Burns.



WARNING: Arc Protective Blankets are not designed for electrical insulating protection. Using the Arc Protective Blanket for electrical insulating protection can result in serious injury or death.

◀ ARC PROTECTION BLANKET

Salisbury by Honeywell Arc Protection Blankets are now available in 4' x 5' and 4' x 8' sizes. Each size is available in 15kA or 40kA ratings. The 15kA blankets include convenient loops and the 40kA blankets include grommets to easily keep the blanket in place. These new blankets are sold individually or with a storage bag or storage bag and tie-strap kit.

The Arc Protection Blanket is used as a barrier for protection from the explosive and incendiary effects of electrical arcs and flashes. These hazardous electrical discharges can be caused by faults in cables, in cable splices and joints, and at transformer terminals, or they may be generated by the operation of switch gear, circuit breakers and lightning arrestors. The blanket can be used for worker protection in underground vaults, switchyards, and other locations where electrical equipment poses a risk of exposure to explosive electrical discharges. **MEETS NEW ASTM F2676 STANDARD.**

NOTE: These products do not eliminate or reduce requirements for proper PPE for arc flash protection

ARC PROTECTION BLANKET

Cat. No.	Dimensions in. (mm)	Description
ARC45-15	48 x 60 (1219 x 1524)	15kA rating - navy blue
ARC45-40	48 x 60 (1219 x 1524)	40kA rating -gray/khaki
ARC48-15	48 x 96 (1219 x 2438)	15kA rating - navy blue
ARC48-40	48 x 96 (1219 x 2438)	40kA rating -gray/khaki
		-Add suffix "P" to include storage bag. -Add suffix "PS" to include storage bag and tie-straps.
		-Add suffix "C" to include P4 canister. -Add suffix "CS" to include P4 canister and tie-straps.
ARC142	1 x 42 (25.4 x 1067)	Single Kevlar Strap w/ Buckle
ARC142-K16		Arc48 Strap Kit With 16 Buckles
ARC142-K12		Arc45 Strap Kit With 12 Buckles

◀ SWITCHBOARD MATTING

Switchboard Matting is placed permanently in front of switchgear, motor control centers and other high voltage apparatus to provide an additional level of protection for electrical workers. Made from high quality Type II material, 1/4" (6.4mm) thick and tested to 20kV to comply with ASTM D178, Class 2 specifications. The corrugated surface acts as a safety tread while reducing the possibility of metal particles becoming embedded. Class 2, switchboard matting is made in 25 yard rolls which can be custom cut to specified lengths as per customer request. Class 4 is sold in full rolls only.

Class 2 Maximum Use Voltage: 17,000 VAC

Class 4 Maximum Use Voltage: 36,000 VAC

SWITCHBOARD MATTING

Cat. No.	Dimensions in. (mm)	Weight lbs. (kgs)
M24-2	1/4 x 24 (6 x 610)	9 (4.1)
M30-2	1/4 x 30 (6 x 762)	12 (5.4)
M36-2	1/4 x 36 (6 x 914)	15 (6.8)
M48-2	1/4 x 48 (6 x 1219)	18 (8.2)
M36-4*	1/2 x 36" x 60 feet long (12 x 914 mm x 18.3 m long)	684 (307.8)

All switchboard matting comply with current ASTM D178 standards

*Sold in full rolls only.



Matting Cross Section