

Best JOGGER / L-7328

Best JOGGER S1P SRC Composite Toe/Kevlar Plate PU/PU Low Ankle Shoe



CE EN ISO 20345:2011 S1P SRC

FEATURES:

- Upper: Breathable blue cow suede leather
- Lining: Breathable & Abrasion resistant sandwich
- Insock: Anti-static breathable EVA insock
- Outsole: PU/PU injection, dual density
- Tested : By UK Intertek lab (Appoved body:0362)
- Toe: Composite toe cap to resist 200 joules impact
- Penetration: Composite plate to resist 1100 newtons puncture

ERP Code: S5020234
Size: 38 – 46

G.Weight: 12kgs/carton
Carton dimension: 62x43x33cm
Cubic meter/Carton: 0.087978
Packing: 10PCS/Carton



200 JOULE TOECAP



SLIP-RESISTANT



SHOCK ABSORPTION



ANTI-STATIC



PETROL AND CHEMICAL RESISTANT



ANTI-NAIL MIDSOLE



OIL RESISTANT



ELECTROSTATIC DISCHARGE

Best JOGGER / L-7328

Best JOGGER S1P SRC Composite Toe/Kevlar Plate PU/PU Low Ankle Shoe



Outsole material:

The outsole is made in PU/PU dual density. The midsole is 45 degree hardness PU, which is soft and shock absorption. The outsole is 60-65 degree hardness PU, which is tough and abrasion resistant. The outsole can pass SRC slip-resistant test.



Insock material:

J-001 insock design, the ventilation fabric can absorb 90% sweat and dry feet efficiently. U-design support heel can disperse human weight pressure, and reduce friction between feet and shoes. EVA material is soft and flexible, to increase comfortability during walk.



Toe protection:

Composite toe cap can reach 200 joules. It is light and anti-magnet, compared with steel toe cap.



Penetration protection:

Kevlar plate, to resist 1100 newtons nail puncture. It is more light, flexible and anti-magnet, compared with steel plate.



SRC		
SRC (SRA+SRB)		
SRA CERAMIQUE + EAU ET	PLAT ≥ 0.32	0.52
	TALON (RELIEF ?) ≥ 0.28	0.48
SRB ACIER + GLYCÉRINE	PLAT ≥ 0.18	0.23
	TALON (RELIEF ?) ≥ 0.13	0.18

EN ISO 20345: 2011

Usage & Storage:

1. Recommended places: Basic workplace, construction, logistics, mechanics, chemical factory, electronic factory, mining, food & Health etc
2. It is very important that shoes selected must be suitable for the right workplace and environment. The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are not valid for fire, water, electric etc.
3. Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with article 10 of the PPE Directive (89/686/EEC) including amendments and corrigendum upto 14/12/2010 for intermediate design category products. This has been shown through satisfactory testing to EN ISO 20345:2011 and examination of the Technical File Documentation.

Best JOGGER / L-7328

Best JOGGER S1P SRC Composite Toe/Kevlar Plate PU/PU Low Ankle Shoe



中国认可
国际互认
检测
TESTING
CNAS L0167

Test Report

No. SL917192970727FW

Date: Mar 23, 2018

Page 1 of 17

SHANGHAI LANGFENG INDUSTRIAL CO., LTD.
ROOM 908, BUILDING 1, LUXIANG ROAD 111, BAOSHANG DISTRICT, SHANGHAI, CHINA

The following samples were submitted and identified on behalf of the client as:

- A. Three pairs of safety shoes in sand (L-7331)
- B. Three pairs of safety shoes in sand (L-7329)
- C. Nine pairs of safety shoes in sand (L-7328)
- D. Three pieces of sand cowhide leather for upper
- E. Black sandwich mesh for vamp/quarter/counter lining from sample A
- F. Black PU for collar from sample A
- G. Black cambrelle + EVA for Insock from sample A
- H. Lace from sample A

Style No	:	L-7331 / L-7328 / L-7329.
Size	:	36# - 48#
Outsole	:	PU/PU
Toecap	:	Plastic Toecap
Insert Plate	:	Composite insert plate
Upper	:	Sand Cowhide Leather
Vamp/Quarter/Counter Lining	:	Black Sandwich Mesh
Collar	:	Black PU
Tongue	:	Black PU
Insole	:	Composite insert plate
Insock	:	Black Cambrelle + EVA
Sample Receiving Date	:	Dec 29, 2017
Test Performing Period	:	Dec 29, 2017-Mar 23, 2018
Test Performed	:	Selected test(s) as requested by applicant against EN ISO 20345: 2011 performance standard.

Test Results : Please refer to the next page(s).

Signed for and on behalf of
SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

Huang Asan
Approved Signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/terms-and-conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-conditions.aspx/terms-conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorised alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (+86-755) 8307 1443, or email: CN_Doccheck@sgs.com
188 Kexu Road, Sanyuanli, Guangzhou Economic and Technology Development Zone, Guangzhou, China 510663 t: (86-20) 82155666 f: (86-20) 82075169 www.sgs.com/en/cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t: (86-20) 82155666 f: (86-20) 82075169 e: sgs.china@sgs.com

Member of the SGS Group (SGS SA)