**BEST TITAN/ M-8179**BEST TITAN/ SBP SRC Steel Toe/ Steel Plate Rubber High Ankle Shoe





Upper: Black cow smooth grain leather Lining: Breathable & Abrasion resistant BK mesh Insock: Hard breathable EVA insock Outsole: Goodyear welted rubber construction Tested: By UK Intertek lab (Appoved body:0362) Toe: Steel toe cap to resist 200 joules impact Penetration: Steel plate to resist 1100 newtons puncture

> ERP Code: S5020132 Size: 38 - 46

G.Weight: 14kgs/carton Carton dimension: 64x48x33cm Cubic meter/Carton: 0.098208 Packing: 10PCS/Carton















200 JOULE TOECAP



SLIP-RESISTANT



SHOCK ABSORPTION



ANTI-STATIC



PETROL AND CHEMICAL RESISTANT



ANTI-NAIL **MIDSOLE** 



OIL RESISTANT

#### BEST TITAN/ M-8179

BEST TITAN SBP SRC Steel Toe/ Steel Plate Rubber High Ankle Shoe



## **Outsole material:**

The outsole is made in PU/PU dual density. The midsole is 45 degree hardness PU, which is soft and shock absorption. The outsole is 60-65 degree hardness PU, which is tough and abrasion resistant. The outsole can pass SRC slip-resistant test.



#### Insock material:

J-001 insock design, the ventilation fabric can absorb 90% sweat and dry feet efficiently. U-design support heel can disperse human weight pressure, and reduce friction between feet and shoes. EVA material is soft and flexible, to increase comfortability during walk.



# Toe protection:

Stainless steel toe cap can reach 200 joules. It is more strong than iron toe cap.



# Penetration protection:

Steel plate, is zero-penetration resistant, which can resist 1100 newtons nail puncture. It is more strong and flexible than normal iron plate.



# SRC (SRA+SRB) Sole 81 PU - PU SRA GERAMIQUE EAÜ ET SOLE 81 PU - PU SRA CERAMIQUE EAÜ ET SOLE 81 PU - PU SRA CERAMIQUE EAÜ ET SOLON MOLINE 7) SOLON BOLON BOLON

# **Usage & Storage:**

- 1. Recommended places: Basic workplace, construction, logistics, mechanics, chemical factory, electronic factory, mining, food & Health etc
- It is very important that shoes selected must be suitable for the right workplace and environment. The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are not valid for fire, water, electric etc.
- Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with article 10 of the PPE Directive (89/686/EEC) including amendments and corrigendum upto 14/12/2010 for intermediate design category products. This has been shown through satisfactory testing to EN ISO 20345:2011 and examination of the Technical File Documentation.



## BEST TITAN/ M-8179

BEST TITAN SBP SRC Steel Toe/ Steel Plate Rubber High Ankle Shoe





Test Report No. SL917192840173FW

Date: Nov 09, 2017

Page 1 of 3

SHANGHAI LANGFENG INDUSTRIAL CO., LTD.
ROOM 908, BUILDING 1, LUXIANG ROAD 111, BAOSHANG DISTRICT, SHANGHAI, CHINA

The following samples were submitted and identified on behalf of the client as:

(A) Two pairs of safety shoes in Brown.

(B) One pairs of safety shoes in Black

Ref. No. : (A) M-8173 (B) M-8179

Size : US 9# Men Insert plate : Steel plate Toecap : Steel toecap

Sole Yellow Rubber/Black Rubber

Upper : Yellow nubuck leather/Black nubuck leather
Vamp Lining : Yellow sandwich mesh/ Black sandwich mesh
Quarter Lining : Yellow sandwich mesh/ Black sandwich mesh

Insole : Non-woven
Collar : Black brace web

Tongue : Yellow cow suede leather/ Black cow suede leather

Insock composition : Black sandwich mesh + EVA

Sample Receiving Date : Nov 06, 2017

Test Performing Period : Nov 06, 2017 ~ Nov 09, 2017

Test Performed : Selected test(s) as requested by applicant against

ASTM F2413-11 performance standard.

Test Results : Please refer to the next page(s).

Signed for and on behalf of SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

Hanson Chen Approved Signatory

This test report refer only to the samples tested



Uness otherwise agreed in witting, this document is issued by the Company subject to its General Conditions of Service princed overlead, available on request or accessible a http://www.goc.com/articlens-end-Conditions\_accessed\_conditions for illections of the http://www.goc.com/articlens-end-Conditions\_accessed\_conditions for illections of Detailable and the service of the servi

Member of the SGS Group (SGS SA)

