


# Shine



Vest Label Ensures Proper Use of Performance Material and Care of Vest

Contrasting Trim Maximizes Daytime Visibility

Retroreflective Material for Night Time Visibility

Fluorescent High Visibility Background Material for Daytime Visibility



## Specifications

ANSI Requirements	ANSI/ISEA 107-2010 Class 2
European Norm	EN ISO 20471:2013
Color	Yellow/Orange
Features	2" Retroreflective tape
Product Type	High Visibility
Size	S1 – S7

**ANSI** ANSI/ISEA 107-2010

The American National Standard for High-Visibility Safety Apparel and Headwear, (ANSI/ISEA 107-2010), which sets the performance criteria for high-visibility apparel. This safety apparel consists of background material, retroreflective material, and combined-performance material:

- Background material is “colored fluorescent material intended to be highly conspicuous, but not intended to comply with the requirements... for retroreflective material.”
- Retroreflective material is “material that reflects and returns a relatively high proportion of light in a direction close to the direction from which it came.”
- Combined-performance material is “retroreflective material that is also a fluorescent material and can be counted toward the minimum area requirements for background material.”

ANSI/ISEA also has three numbered performance classifications for high visibility apparel:

### Performance class 1

- Minimum background material:217 in.<sup>2</sup>
- Minimum retroreflective material: 155 in.<sup>2</sup>
- Provides the minimum amount of required material to distinguish the wearer from the environment.
- Intended for workers whose tasks don't divert their attention from approaching traffic.
- Intended for locations where the worker is separated from traffic, which is traveling no faster than 25 mph.

### Performance class 2

- Minimum background material:775 in.<sup>2</sup>
- Minimum retroreflective material:201 in.<sup>2</sup>
- Provides enhanced visibility during inclement weather.
- Intended for workers whose task divert their attention from approaching traffic and for those who must work near vehicles exceeding 25 mph

### Performance class 3

- Minimum background material:1240 in.<sup>2</sup>
- Minimum retroreflective material:310 in.<sup>2</sup>
- Provides maximum visibility for workers who have tasks that place them in imminent danger from approaching traffic
- Provides maximum visibility when the wearer must be conspicuous at a minimum distance of 1,280 feet.

