



PRODUCT NUMBER: 2091941
ELECTROSOFT CLASS 4

Handling of high voltage to 36 000 volts. Must be used with a leather underglove.

Honeywell

Översikt

Reference Number

2091941

Product Type

Handskar

Range

Electrical Protection

Line

Latex

Brand

Honeywell

Brand formerly known as

ELECTROSOFT

Industry

- Energy or Electricity
- Maintenance
- Telecoms

Product Use

Handling of high voltage to 36 000 volts. To be used with leather protectors for mechanical protection.

Features & Benefits

Feature

Beige natural latex insulating glove

Cut edge

Category AZC

Benefit

COMFORT

Its anatomical shape and lightly powdered interior make it easier to slip the glove on and off.

RESISTANCE

Its natural latex base offers high dielectric characteristics.

Its thickness (3.4 mm) ensures good dexterity while offering protection up to 36,000 volts of use.

SAFETY

It must be used with a leather overglove.

Technical Description

Description

CE CATEGORY : III Irreversible risks
In accordance with standards :
EN 60903-2003
CEI 903-2002

CHARACTERISTICS :

Beige natural latex insulating glove
Category RC
Cut edge

Product Technology

Dipped Gloves

Glove/liner color

Beige

Coating Type

Latex

Length

41 cm

Thickness

3.4 mm

Harmlessness

In conformity with standards

Sizes

10 and 11

Packaging Label

Tagging

CE Honeywell
2091941 XX
EN 60903-2003
CEI 903-2002

Certifications

 E.C. Declaration of Conformity

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Certificate Number

7012

EC Attestation

EC Attestation

EC Attestation Number

7012

Ytterligare information

User Information Sheet

On the polybag

Maintenance

Life Cycle

Gloves that are used frequently should be tested at intervals less than 6 month.

Gloves that are used only occasionally should be tested after each use and, in any case, at intervals of not more than 12 months.

Gloves held in stock should be retested at intervals not exceeding 12 months.

Storage Information

Store in original packaging (Opaque and antiUV packaging used for protection and instructions for use).

Do not compact or fold.

Do not expose to heat sources (sunlight, radiators, artificial light). Store between 10°C and 21°C.

Care Instructions

Inspection : Before each use, carry out a visual inspection and check the glove inflation.

Any puncture or perforation makes the gloves unusable.

Precautions : Do not expose to solvents or chemicals that may cause deterioration. Do not use the glove when damp.

Cleaning : use water and soap. Dry below 65°C with ambient humidity