

*CanaSafe*TM

Protecting Globally, Envisioning the Future...



*iMPactor*TM I

Rugged. Durable. Reliable.

iMPactor I delivers you robust construction packed with features, all at an even more affordable price - iMPactor I - setting standards beyond the norm.



*CanaSafe*TM

iMPactor™ I

HDPE Shell
Provides Excellent
Impact Properties

Replaceable Sweatband









Pushloc & Twizloc Suspension
Options. Twizloc Utilizes
©SwivEL Design - Maintains
Correct Nape Placement"



Textile Suspension
As Standard

Incorporates Canasafe
EAP™ Technology (Energy
Absorbing Points)

iMPactor I uses a high density polyethylene (HDPE) shell impregnated with UV stabilizers. On the inside is the industries most wearer friendly suspension - six textile bands interlocked with EAP™ technology ensures the best impact absorption capability possible, with the option of Pushloc™ or Twizloc™ adjustment systems. Replaceable sweatband is standard.

| | | | | | |
|---|---|---|---|---|---|
|  |  |  |  |  |  |
| Pushloc #45000 | Pushloc #45001 | Pushloc #45003 | Pushloc #45004 | Pushloc #45005 | Pushloc #45006 |
| Twizloc #45020 | Twizloc #45021 | Twizloc #45023 | Twizloc #45024 | Twizloc #45025 | Twizloc #45026 |

| | | | | | | |
|---------|-------|---|---------|---------------------|------|----|
| Pushloc | Size: | 456 x 306 x 690 (WxDxH) mm 18 x 12 x 27.2 inch | Weight: | 8.4 kg 18.5 lbs. | QTY: | 20 |
| Twizloc | Size: | 648 x 463 x 456 (WxDxH) mm 25.5 x 18.2 x 18 inch | Weight: | 9 kg 19.84 lbs. | QTY: | 20 |

 Canasafe Industries Toronto, Ontario, Canada
www.canasafe.com

iMPactor™ I safety helmet meets ANSI / ISEA 289.1 Standard, Type I Class E & G, and CSA 294.1 - 05 Type I Class E & G. Product is LT (Low Temperature) rated and approved for reverse donning ↔